

i62 SIP Door Phone

Description

The i62 is a SIP door phone that integrates access control, intercom, and security functions into one product. It features a elegant design and is equipped with a physical quick-dial button. The i62 meets the high protection standards of IP66 and IK07, ensuring a high level of security suitable for outdoor environments. It supports various door opening methods for streamlined access management and is equipped with a 2 mega-pixel camera for one-touch audio and video communication. Compatible with SIP and ONVIF protocols, it integrates seamlessly with security systems and works well with major mainstream platforms. The i62 can be customized for various scenario solutions, making it suitable for upscale residential areas, office buildings, communities, and industrial parks.

Main Features

One button for quick contact with the management office.

Equipped with a 2 mega-pixel HDR high-definition camera, it provides clearer imaging.

IP66 & IK07 high protection rating, wide temperature operation, suitable for harsh outdoor environments.

Equipped with a wide range of interfaces for connecting various security devices.

Supports the standard ONVIF protocol, providing high flexibility and excellent compatibility.







Fanvil Technology Co., LTD
Add: 13th Floor, Building 2, Runzhi R&D Center, Xin'an Street, Bao'an District, Shenzhen, Guangdong, China
Phone: 0755-26402199 E-mail: sales@fanvil.com Web: www.fanvil.com

Specifications

Panel Type	Multi-apartment，Community，Hotel，Villa
Screen/Keyboard	Quick call button ×1
Body	Aluminum
Colors	Gunmetal
Sensor	1/2.9-inch，COMS
Camera	2 Mpx,Support infrared
Viewing Angle	120°(Horizontal) 60°(Vertical)
Output video	H.264 (Baseline,Main Profile)
Light Sensitivity	0.1Lux
Card Storage	1,0000
Face Storage	1,0000
Power Consumption	PoE: 1.69~6.84W Adapter: 1.42~5.93W
Power Supply	DC 12V / 1A PoE 802.3af Class 3
Working Temperature	-40℃~+70℃
Storage temperature	-40℃~+70℃
Size of the Panel (LWH)	177.4x88x36.15mm
IP / IK Level	IP66 / IK07
Installation	Wall-mounted Flush-mounted(Need to Purchase Accessories Separately：EX102)

Functional Capabilities

Supported Protocols	SIP 2.0 over UDP/TCP/TLS
Lock Opening	IC/ID Card，By DTMF Code，Remote door opening
Interface	Wiegand Input/Output Short Circuit Input/Output RS485 (Reserve) Line out for induction loop
Supported Wiegand	26, 34 bit
Supported ONVIF Types	Profile S
Supported Standards	Mifare Classic 1K/4K，Mifare DESFire，Mifare Ultralight，Mifare Plus Cards 13.56 MHz，Cards 125 kHz
Talking Mode	Full duplex (High-definition Audio)
Additionally	Built-in relay，Open API，Motion detection，Tamper Alarm，TF Card

Fanvil Technology Co., LTD
Add: 13th Floor, Building 2, Runzhi R&D Center, Xin'an Street, Bao'an District, Shenzhen, Guangdong, China
Phone：0755-26402199 E-mail：sales@fanvil.com Web：www.fanvil.com