
DCNM-FBPS Flush blank panel slim
DICENTIS

- Covers 50 mm slots sizes
- Stylish and modern design



The blank panel neatly closes off a slot in a flush mounted unit that is not in use. The panel can be removed if a future expansion requires the available slot. Two different panel widths are available.

Parts included

Quantity	Component
10	DCNM-FBPS Flush blank panel slim

Technical specifications

Mechanical

Mounting type	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with the DCN-FCOUP Flush coupling and the DCNM-FEC Flush end cap in any surrounding
Dimensions	56 mm x 50 mm
Weight (g)	16 g
Color (RAL)	RAL 9017 Traffic black

Environmental

According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

Transportation temperature (ºC)	-30 ºC – 70 ºC
Transportation temperature (ºF)	-22 ºF –158 ºF
Storage temperature (°C)	-5 °C – 45 °C
Storage temperature (°F)	23 °F – 113 °F
Operating relative humidity, non-condensing (%)	5% – 90%

Ordering information

DCNM-FBPS Flush blank panel slim
Blank panel 50 wide, flush mounted, set of 10.
Order number **DCNM-FBPS | F.01U.393.972**

https://www.keenfinity-group.com

© Electro Voice Dynacord 2026