DCNM-FMCP Flush microphone connection panel
DICENTIS



- Stylish and modern design
- Shock-mount technology for less external noise
- The microphone and loudspeaker can be active at the same time
- Sturdy connection to the microphone

The Microphone connection panel connects the pluggable microphones DCNM-MICSLS and DCNM-MICSLL to one of the audio inputs of the Flush base device (DCNM-FBD). The shock-mount principle reduces unwanted sound from tables going into the microphone. The microphone connection panel has a pre-amplifier for the microphone while maintaining GSM immunity and control over the microphone LEDs.

Functions

Interconnections

- Balanced audio interface to connect to the DCNM-FBD (2 m cable with a 3 pole terminal block).
- Power and control interface to the DCNM-FMICB/ DCNM-FPRIOB.

Parts included

Quantity	Component
1	DCNM-FMCP Flush microphone connection panel
1	Power cable
1	Audio cable

Technical specifications

Electrical

Frequency response (-3 dB) (Hz) (-3 dB at nominal level)	125 Hz – 15,000 Hz
Total harmonic distortion + noise (%)	0.10%
Dynamic range (dB)	90 dB
Minimum signal-to-noise ratio (dB)	90 dB

Microphones
According to ISO 22259

Nominal acoustic input level (dB SPL)	80 dB SPL
Maximum acoustic input level (dB SPL)	110 dB SPL

Mechanical

Mounting type	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with the DCN-FCOUP Flush coupling and the DCNM-FEC Flush end cap in any surrounding
Dimensions (H x W x D) (mm)	56 mm x 50 mm x 80 mm
Dimensions (H x W x D) (in)	2.20 in x 2 in x 3.10 in
Weight (g)	70 g
Weight (lb)	0.20 lb
Color (RAL)	RAL 9017 Traffic black

Environmental
According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

Operating temperature (°C)	5 °C – 45 °C
Operating temperature (°F)	41 °F – 113 °F

Transportation temperature (ºC)	-30 ºC – 70 ºC
Transportation temperature (ºF)	-22 ºF – 158 ºF
Storage temperature (°C)	-5 °C – 45 °C
Storage temperature (°F)	23 °F – 113 °F
Operating relative humidity, non-condensing (%)	5% – 90%

Ordering information

DCNM-FMCP Flush microphone connection panel
Flush mounted microphone connection panel.
Order number **DCNM-FMCP | F.01U.383.837**
Z.01X.001.903

Services

EWE-DCNMFP-IW 12 mths wrty ext DICENTIS Flush Panel
12 months warranty extension
Order number **EWE-DCNMFP-IW | F.01U.406.171**

https://www.keenfinity-group.com

© Electro Voice Dynacord 2026